

XL35 MAGNETIC BASE DRILLING MACHINE



- Gearbox mounted motor unit for stability
- Die-cast magnesium alloy body, light weight
- Powerful magnet base
- Double dovetail rail feature to increase stroke
- Integral cooling system.
- Compact size

Core drill dia(mm)	35
Rated voltage(v)	110/220
Rated frequency(Hz)	50-60
Rated input power(w)	1600
No-load speed(rpm)	910
Max attraction(N)	16000
Cutting Depth(mm)	35
Stroke(mm)	210
Packing size(cm)	58x18x37
Net/Gross weight(kgs)	14/17

XL35Ai AUTOMATIC MAGNETIC BASE DRILLING MACHINE



- Fully automatic drilling and return
- Motor stops automatically after returning
- Lightweight, high efficiency, small size
- Feed speed is adjusted automatically according to the load
- Double dovetail rail feature to increase stroke
- Powerful magnet base
- Integrated coolant system

Core drill dia(mm)	35
Rated voltage(v)	110/220
Rated frequency(Hz)	50-60
Rated input power(w)	1600
No-load speed(rpm)	910
Max attraction(N)	16000
Cutting Depth(mm)	30
Stroke(mm)	210
Packing size(cm)	35x25x43
Net/Gross weight(kgs)	14/20.5

ADVANCED CUTTING TECHNOLOGY

HEAD OFFICE

Unit 11, Rotherham Close,
Norwood Industrial Estate,
Sheffield S21 2JU, UK,
Tel +44 (0) 114 331 0008,
Mob +44 (0) 772 161 2656
E sales@advancedcuttingtechnology.com

EUROPE OFFICE

Newtupothouse, Limerick Road,
Mallow, Co. Cork Eire,
Tel; +353 2242 802,
E denis@advancedcuttingtechnology.com

USA OFFICE

1508 State Road, Vermillion,
Ohio USA
Tel; +1 440 967 9300
Fax; +1440 9671301
E ussales@advancedcuttingtechnology.com